

13.08.03



Europäisches  
Patentamt

European  
Patent Office

Office européen  
des brevets



Bescheinigung

Certificate

Attestation

Die angehefteten Unterla-  
gen stimmen mit der  
ursprünglich eingereichten  
Fassung der auf dem näch-  
sten Blatt bezeichneten  
europäischen Patentanmel-  
dung überein.

The attached documents  
are exact copies of the  
European patent application  
described on the following  
page, as originally filed.

Les documents fixés à  
cette attestation sont  
conformes à la version  
initialement déposée de  
la demande de brevet  
européen spécifiée à la  
page suivante.

Patentanmeldung Nr. Patent application No. Demande de brevet n°

02078880.8

**PRIORITY  
DOCUMENT**

SUBMITTED OR TRANSMITTED IN  
COMPLIANCE WITH RULE 17.1(a) OR (b)

Der Präsident des Europäischen Patentamts;  
Im Auftrag

For the President of the European Patent Office

Le Président de l'Office européen des brevets  
p.o.

R C van Dijk



Europäisches  
Patentamt

European  
Patent Office

Office européen  
des brevets

Anmeldung Nr:  
Application no.: 02078880.8  
Demande no:

Anmeldetag:  
Date of filing: 19.09.02  
Date de dépôt:

Anmelder/Applicant(s)/Demandeur(s):

Koninklijke Philips Electronics N.V.  
Groenewoudseweg 1  
5621 BA Eindhoven  
PAYS-BAS

Bezeichnung der Erfindung/Title of the invention/Titre de l'invention:  
(Falls die Bezeichnung der Erfindung nicht angegeben ist, siehe Beschreibung.  
If no title is shown please refer to the description.  
Si aucun titre n'est indiqué se référer à la description.)

Optical disc apparatus

In Anspruch genommene Priorität(en) / Priority(ies) claimed / Priorité(s)  
revendiquée(s)  
Staat/Tag/Aktenzeichen/State/Date/File no./Pays/Date/Numéro de dépôt:

Internationale Patentklassifikation/International Patent Classification/  
Classification internationale des brevets:

G11B7/00

Am Anmeldetag benannte Vertragsstaaten/Contracting states designated at date of  
filing/Etats contractants désignées lors du dépôt:

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR IE IT LI LU MC NL PT SE SK TR

Optical disc apparatus

EPO - DG 1

19. 09. 2002

(55)

Optical disc apparatus for recording and/or reproducing information on/from an information surface of a rotatable optical disc, comprising:

- a supporting assembly;
- a motor, associated with the supporting assembly, for rotating the optical disc about a spindle axis and having a magnetic rotor and a magnetic motor stator magnetically cooperating with each other through an intermediate air gap;
- optical means associated with the supporting assembly for scanning an information surface of the said optical disc and comprising a focussing lens assembly having a movable focussing lens having a focussing axis, said focussing lens assembly being movable in an axial direction along said focussing axis for focussing an optical beam on said information surface of said optical disc (5);
- a swing arm assembly comprising a generally elongate swing arm structure mounting the said focussing lens assembly near a free end, the swing arm assembly being pivotally rotationally movable about a swing axis remote from said free end and directed generally perpendicular to the swing arm structure and generally parallel to the said spindle axis and the said focussing axis, such that the swing arm assembly rotationally sweeps a scanning plane generally parallel to the said information surface of the mounted optical disc, the swing arm assembly thereby causing said focussing lens assembly to scan over the information surface of the mounted optical disc;
- rotational pivoting means for enabling the said rotational scanning movements of the swing arm assembly and comprising stationary pivoting means associated with the supporting assembly and movable pivoting means associated with the swing arm structure pivotally cooperating with the stationary pivoting means;
- movable magnetic scanning means provided at the free end of the swing arm assembly for driving said swing arm assembly rotationally about the said swing axis;
- stationary magnetic scanning means associated with the supporting assembly and comprising a magnetic scanning stator core provided near and spaced from the free end of the swing arm assembly for magnetically cooperating with the said movable magnetic scanning means through at least one intermediate air gap disposed in a curved plane.

An embodiment of such an optical disc apparatus is known from US Patent No. 4,794,586 disclosing a swing arm assembly in which the movable magnetic focussing means and the movable magnetic scanning means comprise two voice coils arranged at the free end of the swing arm assembly, whose windings are crossed to provide both focussing and scanning movements in cooperation with stationary permanent magnetic stator means. The swing arm assembly is pivotally movable about a swing axis which is the central axis of a stationary pivot. To focus the focussing lens, the arm assembly is flexed as a whole by the magnetic focussing force produced by the voice coils provided at the free end of the arm assembly.

The accuracy of scanning movements of the swing arm assembly relative to the information surface of an optical disc which has been placed on a disc support provided on the motor spindle with this kind of prior art optical disc apparatus is dependent on a number of positional and angular tolerances in regard to e.g. the relative positions of the motor spindle, the rotational pivoting means for the swing arm assembly and the position of the stationary magnetic stator means and their angular relative orientations. The motor unit, the swing arm assembly and the stationary magnetic stator means all have to be individually positioned and secured by suitable means relative to the supporting assembly, for example a base plate or frame. As a result of the constant trend for miniaturization which may be observed in the information and communication industry in general, optical disc apparatus are getting ever smaller. As a result the tolerances indicated above for positioning parts on a supporting assembly also have to become smaller, thus increasing the complexity of the manufacturing of the individual parts as well as the assembly of the parts.

It is therefore an object of the invention to provide a novel and useful optical disc apparatus of the above kind which is easier to produce and assemble, which is suitable for but not limited to miniaturized optical disc apparatus and is adaptable to several interesting and advantageous embodiments. With this object in mind the invention provides an optical disc apparatus of the kind described, having the inventive feature that the stationary magnetic scanning means are rigidly associated with the magnetic motor stator.

Thus any inaccuracies in the position of the stationary magnetic scanning means and the motor stator resulting from individual positioning on a supporting assembly are eliminated. The accurate positioning of the stationary magnetic means relative to the

motor stator means may be carried out by the motor manufacturer during the production of the motor under accurately controlled conditions.

Preferably an embodiment of the invention is used wherein the motor stator and the scanning stator core are integrated into a combined stationary unit. Thus the motor stator and the scanning stator core may be manufactured by the motor manufacturer as an integrated unit, eliminating the need to secure and position a separate scanning stator core to the spindle motor.

Preferably a further embodiment of the invention is used, wherein also the stationary pivoting means are rigidly associated with the magnetic motor stator. This eliminates securing and positioning of the stationary pivoting means.

Preferably another embodiment of the invention is used wherein the motor stator, the scanning stator core and the stationary pivoting means are integrated into a combined stationary unit.

Advantageously an embodiment is used wherein the optical disc apparatus  
15 further comprises:

- focussing guiding means for enabling the axial focussing movements of the focussing lens assembly along said focussing axis;
  - movable magnetic focussing means provided at the free end of the swing arm assembly for axially driving said focussing lens assembly along said focussing axis for  
20 focussing the optical beam on the disc information surface;
  - stationary magnetic focussing means associated with the supporting assembly and comprising a magnetic focussing stator core provided near and spaced from the free end of the swing arm assembly for magnetically cooperating with the said movable magnetic focussing means through at least one intermediate air gap disposed in a curved  
25 plane;
- wherein the stationary magnetic focussing means are rigidly associated with the magnetic motor stator.

Preferable is an embodiment of the invention, wherein the motor stator, the scanning stator core, the stationary pivoting means and the focussing stator core are all  
30 integrated into a single combined stationary unit. Thus all the securing and positioning work normally required to secure and position the scanning stator core, the stationary pivoting means and the focussing stator core relative to each other and to the spindle motor are eliminated.

In many cases spindle motors for modern small size optical disc apparatus are provided with a spindle motor comprising a stationary motor spindle inserted in a supporting means such as a base plate, a permanent magnetic rotor being assembled over the spindle. The motor stator is assembled as a stack of individual mutually isolated stator plates which have been cut so as to provide stator teeth on the inside on which stator coils are wound by special machines. The stator is placed over the motor rotor and is centered relative to the rotor by centering means provided on the supporting means.

With this or similar kinds of spindle motor an embodiment of the invention may be used to advantage, wherein the combined stationary unit comprises a scanning stator packet assembled from magnetizable individual stator laminations. In this embodiment the individual stator plates are cut with a motor stator part and a scanning stator part as one piece.

A further important embodiment of the invention is highly suitable to be used with advantage with a motor stator of this or similar kind, wherein:

- the movable magnetic scanning means comprise permanent magnetic rotationally movable scanning means,
- the stationary magnetic scanning means comprise a number of individual stator coils arranged on the stator core in a serial arrangement along the rotational scanning path of the movable permanent magnetic scanning means,
- electronic commutating means being provided to selectively switch stator coils on and off,
- scanning sensor means being provided for detecting, and scanning control means being provided for controlling the rotational position of the arm structure respectively by controlling the current amplitude and direction in each of the stator coils which has been selectively switched on in order to control the rotational arm position and movements.

In this embodiment the scanning stator coils may be provided on the scanning stator core using the same machine that provides the motor stator coils on the motor stator, thus minimizing the assembly effort for assembling the scanning stator coils on the scanning stator core.

A further interesting embodiment of the invention has the feature that:

- the movable magnetic focussing means comprise permanent magnetic axially movable focussing means and
- the stationary magnetic scanning means and the stationary magnetic focussing means comprise a number of individual stator coils arranged on the stator core in a

serial arrangement along the rotational scanning path of the movable permanent magnetic scanning means and distributed over two axially spaced levels,

- focussing sensor means being provided for detecting, and focussing control means being provided for controlling the axial focussing lens position respectively by controlling the current amplitude and direction in each of the stator coils which has been selectively switched on in order to control the axial focussing lens position and movements.

With this embodiment the movable magnetic scanning means as well as the movable magnetic focussing means are permanent magnetic means. This has the obvious advantage that no electrical coils have to be provided on the swing arm structure, thus eliminating the need to provide electrical connecting lines to any coils on the pivotally rotating swing arm structure. All the coils, for scanning as well as for focussing, are on the stationary unit associated with or even integrated with the motor stator and may be provided by the motor manufacturer.

An operational interesting embodiment of an optical disc apparatus of the latter kind may have the feature that

- the stator coils in each of the two levels are spaced at a constant pitch on the stator core along the path rotationally swept by the movable magnetic scanning means and movable magnetic focussing means,

- the stator coils in the two levels are arranged in planes parallel to the scanning plane of the scanning arm structure and

- the stator coils present in one level are positioned between the stator coils present in the other level.

By suitable control of the currents in the coils on the stator core which have been selectively switched on, the focussing lens assembly may be controlled both in the scanning direction and in the focussing direction for following a track on the information surface of a rotating optical disc with the laser spot emanating from the focussing lens. Suitable control of the commutating means may further provide scanning movements of larger amplitude from one area on the information disc to a further area spaced at a distance from the one area.

In cases wherein the movable scanning and/or focussing means are permanent magnetic means a further interesting embodiment of the invention may be used wherein biasing means are provided to bias the magnetic attraction force produced between the movable permanent magnetic scanning and/or focussing means and the motor stator, whereby magnetic adhesion of the scanning arm structure to the motor stator is prevented in a

rotationally extreme position of the scanning arm structure nearest to the spindle motor. This will prevent magnetic adhesion of the scanning arm structure against the motor stator, which may be too strong to overcome by the scanning stator coils.

5 An advantageous embodiment which provides the said biasing means without adding any separate parts to the optical disc apparatus has the feature that:

- the stator core is provided with stator teeth,
- the stator coils are wound on the stator teeth and
- the biasing means are provided by one or more stator teeth on the said stator

10 core, positioned in such a way that in the said extreme rotational position of the scanning arm structure the rotational magnetic pull of the said one or more stator teeth exceeds the rotational magnetic pull of the motor stator.

Also provided is an interesting further alternative embodiment of the invention, wherein:

15 - the movable magnetic scanning means comprise a cylindrical scanning coil having a generally rectangular shape in cross section and having a central opening, two pairs of parallel outer side surfaces, two pairs of inner side surfaces and outwardly facing axial end surfaces at the axially spaced ends of the coil,

20 - the movable focussing means comprising two cylindrical focussing coils having a generally rectangular shape in cross section and having a central opening, two pairs of parallel outer side surfaces, two pairs of inner side surfaces and outwardly facing axial end surfaces at the axially spaced ends of the coil,

- the scanning coil being bonded with one of its outer side surfaces against the free end of the swing arm structure in a position with its central axis generally parallel to the scanning movements of the swing arm,

25 - each focussing coil being being bonded at a part of one of its outwardly facing axial end surfaces at one side of its central opening against the outer side surface of the scanning coil which is remote from the swing arm structure, the two focussing coils being disposed in such a way that the said parts of their outwardly facing axial end surfaces are near to each other, parallel to each other and generally parallel to the scanning movements of  
30 the swing arm,

- the combined stationary magnetic means comprising an elongate permanent magnet means facing the movable focussing coils and spaced from the focussing coils by the said air gap, and further comprising a magnetically permeable stator supporting the permanent magnetic means and having a stator part passing through the central opening of



the scanning coil with play, the permanent magnet means being magnetically polarized in a radial direction relative to the swing axis of the swing arm assembly and the arrangement being such that a substantially radially directed permanent magnetic field is set up over the said air gap.

5           With this embodiment it is the stationary scanning means and focussing means which are permanently magnetic which may be preferred in some cases. A single combined permanent magnetic stationary magnetic means is provided on the magnetically permeable stator which may be integrated with the motor stator as before and may be comprised of a stack of individual stator plates as before, etc. A very efficient light weight coil arrangement  
10 is provided on the movable arm structure for scanning as well as for focussing.

The objects and features of the present invention will become more apparent by referring to the following non-limiting description of a few preferred embodiments given  
15 with reference to the accompanying drawings in which:

Fig. 1 is a schematic plan view of an optical disc apparatus of miniaturized dimensions,

Fig. 2 is a schematic perspective fragmentary view of the optical disc apparatus of Fig.1,

20           Fig. 3-5 are plan views of individual stator laminations of the combined motor and focussing/scanning stator of the optical disc apparatus of Fig.1-2,

Fig.6 is a side view of a stack of stator laminations shown individually in Fig.3-5,

Fig.7 is a perspective view of the stacked stator laminations from Fig.6,

25           Fig.8 is a fragmentary plan view illustrating alternative biasing means to bias a swing arm structure magnetically away from a spindle motor stator,

Fig.9 is a block diagram of the electronic circuitry for the course and fine control of the rigid swing arm focussing and scanning positions,

Fig.10 is a schematic perspective view similar to Fig.2 but of an alternative  
30 embodiment of an optical disc apparatus and

Fig.11 is a perspective exploded view of the arrangement of electrical coils used to control the rigid swing arm scanning and focussing movements of the optical disc apparatus of Fig.10.

Referring to Fig.1 and 2 of the drawing, an optical disc apparatus 1 is shown for recording and/or reproducing information on/from an information surface 3 of a rotatable optical disc 5. The optical disc apparatus 1 is of miniaturized dimensions and is shown in Fig.1 to approximately true scale. The optical disc has a diameter in the order of approximately 23 mm.

The optical disc apparatus 1 comprises a supporting assembly 7 which in the embodiment shown is a printed circuit board measuring some 30 x 40 mm. A spindle motor 9 is associated with the supporting assembly 7 and has a spindle 11 with a spindle axis 13 for rotating the optical disc 5 mounted on the spindle 11 about the spindle axis 13. The spindle motor 9 comprises a permanent magnetic rotor 15 and a magnetic motor stator 17, magnetically cooperating with each other through an intermediate air gap 19.

Optical means are associated with the supporting assembly 7 for scanning the information surface 3 of the optical disc 1 mounted on the spindle 11. The optical means comprise a diode laser unit 21, a beam splitter 23, a collimator lens 25, a 90° reflecting element 27, a focussing lens assembly 29 comprising a lens mount 31 and a movable focussing lens 33 having a focussing axis 35, the focussing lens assembly 29 being movable in an axial direction along focussing axis 35. The optical means further comprise a so called servo lens 37 and a photo sensitive array 39. All these optical elements are well known to the man skilled in the art of optical disc apparatus and will not be explained in detail here. The photodiode laser unit 21 emits a laser beam 42 which is split by the beam splitter 33. Part of the beam is directed to the 90° reflecting element 27 and is shaped by the collimator lens. The laser beam is reflected by the 90° reflecting element 27 and projected through the focussing lens 33 onto the information surface 3 of the optical disc 5. The beam modulated by the data present in the rotating disc 5 is reflected by the information surface 3 and returns through the focussing lens 33, is reflected by the 90° reflecting element 27, passes through the collimator lens 25 and at least partly through the beam splitter 23 and impinges on the photo sensitive array 29. The output signals of the photo sensitive array 29 are output to electronics circuits to derive the data signals representing the data read out from the information surface 3 of the optical disc 5 and to extract the error signals needed to control the position and the movements of the optical assembly relative to the information surface 3 of the optical disc 5.

The optical assembly 21-39 described above is provided in a swing arm assembly 41 comprising a generally elongate swing arm structure 43 mounting the said focussing lens assembly 31-33 near a free end 45, the swing arm assembly 41 being pivotally

rotationally movable about a swing axis 47 remote from said free end 45 and directed generally perpendicular to the swing arm structure 42 and generally parallel to the said spindle axis 13 and the said focussing axis 35 such that the swing arm assembly 41 rotationally sweeps a scanning plane generally parallel to the said information surface 3 of the mounted optical disc 5, the swing arm assembly thereby causing said focussing lens assembly 31-33 to scan over the information surface 3 of the mounted optical disc 5.

Rotational pivoting means 49-53 are provided for enabling the said rotational scanning movements of the swing arm assembly 41 and comprising stationary pivoting means 49 associated with the supporting assembly 7 and movable pivoting means 51 associated with the swing arm structure 43 pivotally cooperating with the stationary pivoting means 51. In the present embodiment the stationary pivoting means 49 and the rotational pivoting means 51 are permanently connected to each other by a deflectable leaf spring 53, which allows pivoting movements of the swing arm assembly 41 in the scanning direction parallel to the information surface 3 of the optical disc 5 only.

15 Movable magnetic scanning means 55-57 are provided at the free end of the swing arm assembly 41 for driving the swing arm assembly rotationally about its swing axis 47. In the present embodiment the movable magnetic scanning means comprises two adjacent permanent magnets 55 and 57 respectively which have been fixed on the free end of the swing arm structure 43 by suitable means such as an adhesive. The permanent magnets 55,57  
20 are magnetized in parallel opposite directions (indicated by arrows in Fig.2) basically along a magnetic axis parallel to the general extension of the swing arm assembly 41.

Stationary magnetic scanning means are provided associated with the supporting assembly 7 and comprising a magnetic scanning stator core 59 provided near and spaced from the free end of the swing arm assembly 41 for magnetically cooperating with the  
25 movable magnetic scanning means 55,57 through an intermediate air gap 61 disposed in a curved plane 63 (see more particularly Figure 3 which will be discussed below).

The embodiment of the invention shown in Figures 1-2 is of a kind in which the pivoting means 49-51 discussed above for enabling scanning movements of the swing arm assembly are second pivoting means, first pivoting means being provided for enabling  
30 focussing movements of the said focussing lens assembly 29. These first pivoting means resemble the already discussed second pivoting means in that they comprise a leaf spring 65 which is fixed to an end part 67 of the swing arm structure 43 on one side and to the movable pivoting means 51. The movable pivoting means 51 thus form an intermediate element between the two leaf springs 53 and 65. The leaf spring 65 is oriented such that it will allow

movements of swing arm structure 41 such that the focussing lens 33 may move along the focussing axis 35 only.

The movable magnetic scanning means 55-57 also operate as movable magnetic focussing means provided near the said free end 45 of the swing arm assembly 41 for driving the focussing lens 33 along the focussing axis 35 to focus the optical beam 42 on the optical disc information surface 3 and thus form combined movable magnetic focussing/scanning means 55-57. Stationary magnetic focussing means are present associated with the supporting assembly 7 for magnetically cooperating through the intermediate air gap 61 with the said combined movable magnetic focussing/scanning means 55-57 for generating a magnetic force vector having a vector component  $F$  parallel to the focussing axis 35 for driving the focussing lens assembly 29 along the focussing axis 35. These stationary magnetic focussing means are combined with the stationary magnetic scanning means and will be discussed below in connection with figures 2-8.

A feature of the embodiment of the optical disc apparatus of Figures 1-2 which is the subject matter of a co-pending application PHNL020898 (Applicant's identification number), having the same priority date as the present application and which is herewith incorporated in the present application by reference, is that the swing arm structure 43 is rigid from the free end 45 up till at least near the swing axis 47 and that the first pivoting means 51, 65, 67 are provided at or near the second pivoting means 49, 51, 53. The swing arm structure 43 is shown more particularly in Fig. 2 as a box like structure housing the optical means 21-33, the lens mount 31 being a fixed element rigidly connected to the swing arm structure 43. However, alternative solutions may appear to the man skilled in the art. The swing arm structure could for example be shaped as rigid profiled beam carrying the optical means 21-33 on the outside. Part of the optical means could be located outside of the swing arm structure and communicate with the remaining means present on or in the swing arm structure through optical, electrical or other connections. The swing arm structure of the optical disc apparatus 1 of Fig. 1-2 has very small dimensions in the order of 2x2x16 mm.

According to a feature of the present invention, the stationary magnetic scanning means or magnetic scanning stator core 59 is rigidly associated with the magnetic motor stator 17. In fact, in the embodiment of Fig. 1-2, the motor stator 17 and the scanning stator core 59 are integrated into a combined stationary unit. Also, the stationary pivoting means 49 are rigidly associated with the magnetic motor stator 17. In fact, the motor stator 17, the scanning stator core 59 and the stationary pivoting means 49 are all integrated into a combined stationary unit. As has been discussed before, with the embodiment according to

Fig. 1-2, the stationary magnetic focussing means are combined with the stationary magnetic scanning means, so that in Fig.1-2 the motor stator, the scanning stator core, the stationary pivoting means and a focussing stator core are all integrated into a combined stationary unit.

Referring now more particularly to Fig. 3-6, the combined stationary unit  
5 comprises a stator packet assembled from magnetizable individual stator laminations of three different kinds referred to by the reference numbers 69, 71 and 73 respectively. In the case of the embodiment of the invention according to Fig. 1-2, the movable magnetic scanning means comprise permanent magnetic rotationally movable scanning means 55,57 and the stationary magnetic scanning means comprise a number of individual stator coils 75 (six coils) arranged  
10 on the stator core 59 in a serial arrangement along the rotational scanning path of the movable permanent magnetic scanning means 55,57. Electronic commutating means are provided (to be discussed later) to selectively switch individual stator coils 75 on and off, scanning sensor means 79 (five sensors) being provided for detecting and scanning control means (to be discussed later) being provided for controlling the rotational position of the arm  
15 structure 43 respectively by controlling the current amplitude and direction in each of the stator coils 75 which has been selectively switched on in order to control the rotational arm position and movements.

In the embodiment of the invention according to fig.1-2 the movable magnetic focussing means comprise permanent magnetic axially movable focussing means also  
20 comprised of the permanent magnets 55,57, the stationary magnetic scanning means and the stationary magnetic focussing means comprising a number of individual stator coils 75 (six coils) and 77 (six coils) arranged on the stator core in a serial arrangement along the rotational scanning path of the movable permanent magnetic scanning means 55,57 and distributed over two axially spaced levels. Focussing sensor means are provided in the photo  
25 sensitive array 39 for detecting the focussing position of the focussing lens 33 in the usual way. Focussing control means and scanning control means (to be discussed later on) are provided for controlling the axial focussing lens 33 position and the angular position of the swing arm assembly 41 respectively by controlling the current amplitude and direction in each of the stator coils 75,77 which have been selectively switched on in order to control the  
30 axial focussing lens position and movements. The stator coils 75,77 in each of the two levels are spaced at a constant pitch on the stator core 59 along the path rotationally swept by the movable magnetic scanning means and movable magnetic focussing means 55,57. The stator coils 75,77 in the two levels are arranged in planes parallel to the scanning plane of the

scanning arm structure and the stator coils 75 present in one level are positioned between the stator coils 77 present in the other level.

Figures 3-6 illustrate how both the motor stator core 17 of the spindle motor 9 and the scanning stator core 59 of the stationary magnetic scanning/focussing means may be assembled from individual stator laminations 69, 71 and 73. As customary, the stator laminations consist of individual parts stamped from soft iron plate material, covered on both sides with an electrically isolating coating or film to prevent eddy currents from flowing between the individual laminations. Each of the laminations 69-73 is provided with an annular part 81 provided with inwardly projecting angularly evenly spaced teeth parts. Stator plates 69 are provided with a curved part 85 extending from and integral with the annular part 81 and provided with mutually evenly spaced teeth parts 87. Stator plates 73 are similarly configured with a curved part 89 having teeth parts 91 at offset positions from the teeth parts 87 but having the same mutual spacing or pitch. Stator plates 73 are provided with a curved part 93 configured similarly to curved parts 85 and 89 but not having teeth parts. The combined spindle motor/scanning stator is assembled by stacking for example six of the laminations 69 on three laminations 71 on six laminations 73, the teeth parts 83, 87 and 91 thus forming eight stator teeth 95 for eight motor stator coils 97, as well as six teeth for the six coils 75 and six teeth for the six coils 77 for the scanning stator core 59 respectively. The axial separation of the two rows of coils 75,77 being provided by the intermediate laminations 93.

Biasing means 99 formed by a small permanent magnet are provided to bias the magnetic attraction force produced between the movable permanent magnetic scanning/focussing means 55,57 and the motor stator 17, whereby magnetic adhesion of the scanning arm structure 43 to the motor stator 17 is prevented in a rotationally extreme position of the scanning arm structure 43 nearest to the spindle motor 9. The magnetic field of the permanent magnet 99 interacts with the magnetic fields of the permanent magnets 55,57 in a repellant way such, that the scanning arm structure 43 will be prevented to adhere magnetically to the spindle motor 9.

In the optical disc apparatus 1 according to the embodiment of Fig.1-2, the motor stator 17, the scanning/focus-sing stator core 59, as well as the stationary pivoting means 49 are all integrated into a combined stationary unit. Referring now more particularly to Fig. 3-7, to this end the laminations 71 are provided with a further extension 101 at the free end of the curved part 93 and at an appropriate angle to the curved part 93 of for example approximately  $90^{\circ}$ . The stacked extensions 101 of the laminations 71 form a supporting beam

while the stacked laminations 69 and 73 form the mutually offset stator teeth 105 and 107 respectively of the scanning stator core 59. The way of securing the leaf springs 53 and 65 between the swing arm structure 43 and the rotating pivoting means 51 and between the pivoting means 51 and the stationary pivoting means 49 at the free end of the supporting beam 103 respectively has been shown in Fig.1-2 only schematically. The leaf springs could be secured by any of a variety of methods known to the man skilled in the art such as by adhesive means, laser welding, spot welding, mechanical clamping, by screws or rivets, etc.

Fig. 8 is illustrative of an embodiment of the invention which has been slightly modified in comparison with the embodiment of Fig.1-7. Only details will be discussed which are typical of this modified embodiment. With this modified embodiment the biasing means 99 are no longer required. Instead, the biasing means are provided by one or more stator teeth 105, 107 on the scanning stator core 59, positioned in such a way that in the said extreme rotational position of the scanning arm structure 43 the rotational magnetic pull of the said one or more stator teeth 105, 107 on the rotating permanent magnetic scanning means 55, 57 exceeds the rotational magnetic pull of the motor stator 17. This is accomplished by widening the air gap 61 between stator teeth 55, 57 and the rotating permanent magnetic scanning means 55, 57 in the vicinity of the motor stator 17. As a result, the magnetic pull P exerted by the stator teeth 55, 57 will exceed the magnetic pull of the motor stator 17 in any position of the swing arm structure 43.

Referring now to the block diagram of Fig.9, a brief discussion will be given regarding the electronic course and fine control of the rigid swing arm angular and focussing positions. The five magnetic field sensors 79, for example of the Hall sensor type or any other suitable type, sense the magnetic fields of the movable permanent magnetic scanning/focussing means 55, 57 and produce electrical magnetic field signals 109 representative of the magnetic field strength and direction sensed. The five signals 109 are input to a magnetic field signal processing unit 111 in which the swing arm angular and focussing position is determined. From this unit a swing arm position signal is output which is input to a coil selection and polarity unit 115. Also input to the coil selection and polarity unit are a focus control signal and tracking control signal 119. These signals are derived from the focus control and tracking control signals provided by the control circuitry (not shown) connected to the photosensitive array 39 which may be largely conventional. The focus control and tracking control signals are used for the fine controlling of the position of the laser beam spot produced by the focussing lens 33 relative to a track of the information surface 3 of the optical disc 5 of the optical disc apparatus 1. The coil selection and polarity

unit 115 has twelve outputs 121, one connected to each of the twelve coils 75, 77 of the stationary magnetic scanning means. The operation of the coil selection and polarity unit during normal operation of the optical disc apparatus 1 is such that only the coils are selected that are actively needed for the fine controlling of the swing arm position relative to the nominal current position of the swing arm relative to the tracks in the information surface 3 of the optical disc sensed by the magnetic field sensors 79. Only a selected few of the outputs 121 is switched on in any such nominal current position. These outputs are controlled by the coil selection and polarity unit in amplitude and polarity in a way suitable to achieve the necessary fine focussing and tracking control. The twelve outputs 121 from the coil selection and polarity unit are connected to twelve corresponding inputs of twelve coil driving circuits provided in a coil driving unit 123, which coil driving circuits operate to amplify the output signals of the coil selection and polarity unit to a level suitable for generating the required magnetic fields in each of the selected coils 75, 77 which are active in the current arm position.

Different embodiments may be used with the invention. Referring now to Fig. 10, an embodiment will be described comprising an optical disc apparatus 125 with an optical disc having an information surface 129 and further comprising a supporting assembly 131. The dimensions may be similar to those of Fig. 1-7 while a number of constituent parts are also similar and will therefore not be described in detail. A spindle motor 133 is provided

for rotating the optical disc 127. A swing arm assembly 135 comprises a swing arm structure 137 containing a number of optical components like the swing arm assembly 41 of Fig. 2, among which a focussing lens 139 mounted on a lens mount 141. The focussing lens 139 is movable along a focussing axis 143 and the swing arm assembly is pivotable around a swing axis 145 parallel to the focussing axis 143. Leaf springs 147 and 149 are provided for enabling pivoting focussing and scanning movements of the entire rigid swing arm structure 137 respectively, relative to an intermediate part 151 and stationary pivoting means 153 respectively. The movable magnetic scanning means comprise a cylindrical scanning coil 155 having a generally rectangular shape in cross section and having a central opening 157, two pairs of parallel outer side surfaces 159, 161 and 163, 165 respectively, two pairs of inner side surfaces 167, 169 and 171, 173 respectively and outwardly facing axial end surfaces 175, 177 respectively at the axially spaced ends of the coil. The movable focussing means comprising two substantially identical cylindrical focussing coils 179A, 179B respectively having a generally rectangular shape in cross section and having a central opening 181, two pairs of parallel outer side surfaces 183, 185 and 187, 189 respectively, two pairs of inner



side surfaces 191, 193 and 195, 197 respectively and outwardly facing axial end surfaces 199, 201 respectively at the axially spaced ends of the coil. The scanning coil 155 has been bonded with its outer side surface 159 against the free end 203 of the swing arm structure 137 in a position with its central axis 205 generally parallel to the scanning movements of the swing arm assembly 135, using suitable means such as adhesive means. Each focussing coil 179A,B has been being bonded at a part of its outwardly facing axial end surface 199 at one side of its central opening 181 against the outer side surface 161 of the scanning coil 155 which is remote from the swing arm structure 137 using suitable bonding means such as adhesive means, the two focussing coils 179A,B being disposed in such a way that the said parts of their outwardly facing axial end surfaces 199 are near to each other, parallel to each other and generally parallel to the scanning movements of the swing arm assembly 135. Combined stationary magnetic means comprise an elongate permanent magnet means 207 facing the movable focussing coils 179A,B and spaced from the focussing coils 179A,B by an air gap, and further comprising a magnetically permeable stator 209 supporting the permanent magnetic means 207 and having a stator part 211 passing through the central opening 157 of the scanning coil 155 with play, the permanent magnet means 207 being magnetically polarized in a radial direction relative to the swing axis 145 of the swing arm assembly 135 and the arrangement being such that a substantially radially directed permanent magnetic field is set up over the air gaps which are present between the scanning coil and the stator part 211 and between the said parts of the focussing coils 179A,B and the stator 209 respectively. In accordance with the invention, the stationary magnetic scanning means 207-211 are rigidly associated with the magnetic motor stator of the spindle motor 133. In accordance with a further feature according the invention, the motor stator of the spindle motor 133, the scanning stator core part 211, the stationary pivoting means 153 and the focussing stator core 209 are integrated into a combined stationary unit. This stationary unit is made from a suitable magnetically permeable material such as soft iron and comprises a temporarily removable part, the part 211, to enable insertion in the central opening 157 of the scanning coil 155. The stationary unit is provided with a supporting beam part having the same thickness as the remaining parts of the stationary unit 209, 211, 213 carrying the stationary pivoting means 153 at its free end and may be comprised of a stack of stator laminations which may be integrated with the motor stator of the spindle motor 133.

Thus two optical disc apparatus 1 and 125 have been described according to a best mode for carrying out the invention contemplated by the inventor at the time of writing the present specification. It will be appreciated by persons skilled in the art that the invention

however is not limited by what has been particularly described and shown above. Many modifications are possible without departing from the inventive concepts herein. The swing arm structure 43 does not need to be rigid over its entire length and the focussing lens assembly could be mounted resiliently on a rigid part of the swing arm structure, the resilient mounting allowing focussing movements. The scanning pivoting means could be of a conventional fulcrum type. The focussing lens assembly could comprise a multiple component assembly including one or more relatively movable optical elements. The pivoting means could comprise swiveling means of gimbal type to provide both scanning and focussing movements. Separate scanning and focussing structures could be provided associated with the spindle motor. The optical means could be provided partly on the supporting structure while being optically and/or electrically coupled with the focussing lens assembly, etc. All these and other embodiments may be combined with the main feature of the invention, which is to have the stationary magnetic scanning means and possibly also the stationary magnetic focussing means and/or the stationary pivoting means rigidly associated with the magnetic motor stator.

## CLAIMS:

19. 09. 2002

(55)

1. Optical disc apparatus for recording and/or reproducing information on/from an information surface of a rotatable optical disc, comprising:

- a supporting assembly;

5 - a motor, associated with the supporting assembly, for rotating the optical disc about a spindle axis and having a magnetic rotor and a magnetic motor stator magnetically cooperating with each other through an intermediate air gap;

- optical means associated with the supporting assembly for scanning an information surface of the said optical disc and comprising a focussing lens assembly having a movable focussing lens having a focussing axis, said focussing lens assembly being  
10 movable in an axial direction along said focussing axis for focussing an optical beam on said information surface of said optical disc;

- a swing arm assembly comprising a generally elongate swing arm structure mounting the said focussing lens assembly near a free end, the swing arm assembly being pivotally rotationally movable about a swing axis remote from said free end and directed  
15 generally perpendicular to the swing arm structure and generally parallel to the said spindle axis and the said focussing axis, such that the swing arm assembly rotationally sweeps a scanning plane generally parallel to the said information surface of the mounted optical disc, the swing arm assembly thereby causing said focussing lens assembly to scan over the information surface of a mounted optical disc;

20 - rotational pivoting means for enabling the said rotational scanning movements of the swing arm assembly and comprising stationary pivoting means associated with the supporting assembly and movable pivoting means associated with the swing arm structure pivotally cooperating with the stationary pivoting means;

- movable magnetic scanning means provided at the free end of the swing arm  
25 assembly for driving said swing arm assembly rotationally about the said swing axis;

- stationary magnetic scanning means associated with the supporting assembly and comprising a magnetic scanning stator core provided near and spaced from the free end of the swing arm assembly for magnetically cooperating with the said movable magnetic scanning means through at least one intermediate air gap disposed in a curved plane;

wherein the stationary magnetic scanning means are rigidly associated with the magnetic motor stator.

2. Optical disc apparatus according to claim 1, wherein the motor stator and the scanning stator core are integrated into a combined stationary unit.

3. Optical disc apparatus according to claim 1 or 2, wherein also the stationary pivoting means are rigidly associated with the magnetic motor stator.

4. Optical disc apparatus according to claim 2 and 3, wherein the motor stator, the scanning stator core and the stationary pivoting means are integrated into a combined stationary unit.

5. Optical disc apparatus according to any of claims 1 to 4, wherein the optical disc apparatus further comprises:

- focussing guiding means for enabling the axial focussing movements of the focussing lens assembly along said focussing axis;

- movable magnetic focussing means provided at the free end of the swing arm assembly for axially driving said focussing lens assembly along said focussing axis for

focussing an optical beam on the disc information surface;

- stationary magnetic focussing means associated with the supporting assembly and comprising a magnetic focussing stator core provided near and spaced from the free end of the swing arm assembly for magnetically cooperating with the said movable magnetic focussing means through at least one intermediate air gap disposed in a curved plane;

wherein the stationary magnetic focussing means are rigidly associated with the magnetic motor stator.

6. Optical disc apparatus according to claims 4 and 5, wherein the motor stator, the scanning stator core, the stationary pivoting means and the focussing stator core are integrated into a combined stationary unit.

7. Optical disc apparatus according to any of claims 2-4 or 6, wherein the combined stationary unit comprises a stator packet assembled from magnetizable individual stator laminations.

- 5 8. Optical disc apparatus according to claim 7, wherein:
- the movable magnetic scanning means comprise permanent magnetic rotationally movable scanning means,
  - the stationary magnetic scanning means comprise a number of individual stator coils arranged on the stator core in a serial arrangement along the rotational scanning
  - 10 path of the movable permanent magnetic scanning means,
  - electronic commutating means being provided to selectively switch stator coils on and off,
  - scanning sensor means being provided for detecting, and scanning control means being provided for controlling the rotational position of the arm structure respectively
  - 15 by controlling the current amplitude and direction in each of the stator coils which has been selectively switched on in order to control the rotational arm position and movements.
9. Optical disc apparatus according to claim 8, wherein:
- the movable magnetic focussing means comprise permanent magnetic axially
  - 20 movable focussing means and
  - the stationary magnetic scanning means and the stationary magnetic focussing means comprise a number of individual stator coils arranged on the stator core in a serial arrangement along the rotational scanning path of the movable permanent magnetic scanning means and distributed over two axially spaced levels,
  - 25 - focussing sensor means being provided for detecting, and focussing control means being provided for controlling the axial focussing lens position respectively by controlling the current amplitude and direction in each of the stator coils which have been selectively switched on in order to control the axial focussing lens position and movements.
- 30 10. Optical disc apparatus according to claim 9, wherein:
- the stator coils in each of the two levels are spaced at a constant pitch on the stator core along the path rotationally swept by the movable magnetic scanning means and movable magnetic focussing means,

- the stator coils in the two levels are arranged in planes parallel to the scanning plane of the scanning arm structure and
- the stator coils present in one level are positioned between the stator coils present in the other level.

5

11. Optical disc apparatus according to any of claims 8-10, wherein biasing means are provided to bias the magnetic attraction force produced between the movable permanent magnetic scanning and/or focussing means and the motor stator, whereby magnetic adhesion of the scanning arm structure to the motor stator is prevented in a rotationally extreme position of the scanning arm structure nearest to the spindle motor.

10

12. Optical disc apparatus according to claim 11, wherein:

- the stator core is provided with stator teeth,
- the stator coils are wound on the stator teeth and

15

- the biasing means are provided by one or more stator teeth on the said stator core, positioned in such a way that in the said extreme rotational position of the scanning arm structure the rotational magnetic pull of the said one or more stator teeth exceeds the rotational magnetic pull of the motor stator.

20

~~13. Optical disc apparatus according to any of claims 1-7, wherein:~~

~~- the movable magnetic scanning means comprise a cylindrical scanning coil having a generally rectangular shape in cross section and having a central opening, two pairs of parallel outer side surfaces, two pairs of inner side surfaces and outwardly facing axial end surfaces at the axially spaced ends of the coil,~~

25

~~- the movable focussing means comprising two cylindrical focussing coils having a generally rectangular shape in cross section and having a central opening, two pairs of parallel outer side surfaces, two pairs of inner side surfaces and outwardly facing axial end surfaces at the axially spaced ends of the coil,~~

30

~~- the scanning coil being bonded with one of its outer side surfaces to the free end of the swing arm structure in a position with its central axis generally parallel to the scanning movements of the swing arm,~~

~~- each focussing coil being bonded at a part of one of its outwardly facing axial end surfaces at one side of its central opening against the outer side surface of the scanning coil which is remote from the swing arm structure, the two focussing coils being~~

disposed in such a way that the said parts of their outwardly facing axial end surfaces are near to each other, parallel to each other and generally parallel to the scanning movements of the swing arm,

- the combined stationary magnetic means comprising an elongate permanent magnet means facing the movable focussing coils and spaced from the focussing coils by the said air gap, and further comprising a magnetically permeable stator supporting the permanent magnetic means and having a stator part passing through the central opening of the scanning coil with play, the permanent magnet means being magnetically polarized in a radial direction relative to the swing axis of the swing arm assembly and the arrangement being such that a substantially radially directed permanent magnetic field is set up over the said air gap.

## ABSTRACT:

(55)

An optical disc apparatus (1) comprising a supporting assembly (7), a spindle motor(9) having a magnetic motor stator (17), optical means for scanning an information surface of the said optical disc mounted on the spindle and comprising a focussing lens assembly (29) having a movable focussing lens, a swing arm assembly (41) comprising a  
5 generally elongate swing arm structure (43) mounting the said focussing lens assembly near a free end (41), movable magnetic scanning means provided at the free end of the swing arm assembly for driving said swing arm assembly rotationally about a swing axis (47) for scanning the disc information surface and stationary magnetic scanning means associated with the supporting assembly and comprising a magnetic scanning stator core (59) provided  
10 near and spaced from the free end of the swing arm assembly for magnetically cooperating with the said movable magnetic scanning means through at least one intermediate air gap disposed in a curved plane. The stationary magnetic scanning means are rigidly associated with the magnetic motor stator.

15 Fig. 2






Fig.1

2/9




Fig.2

3/9




Fig.3




Fig.5



Fig.6

4/9




Fig.4




Fig.7




Fig. 8




Fig.9

8/9




Fig.10






Fig.11

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**